




# JMC-260MA(7104)

## SUBMINIATURE HERMETICALLY SEALED LATCHING RELAY



### ENVIRONMENTAL CONDITIONS:

Temperature Range: -65~+125°C  
 Relative Humidity: 98% at +40°C  
 Atmospheric Pressure: 86~106kPa, Low pressure 4.4kPa  
 Shock: 980m/s<sup>2</sup>  
 Vibration: 10~3000Hz, 294m/s<sup>2</sup>  
 Liner Acceleration: 735 m/s<sup>2</sup>

### Ordering Information:

JMC-260MA / 012 - 0 1

1                    2                    3                    4

1. Model
2. Part No.
3. Mounting Style
4. Terminal Type: 1=Wire Lead (sp)

### TECHNICAL DATA:

Contact Arrangement: 2 Form C (DPDT)  
 Coil Voltage: 12~27VDC  
 Coil Dissipation: ≤0.8W  
 Insulation Resistance: 1000MΩ  
 Dielectric Withstanding Voltage (RMS/50Hz): 500Vr.m.s.  
 Contact Resistance: ≤0.05Ω  
 Operate Time: ≤8ms  
 Bounce Time: ≤5ms  
 Contact Ratings: 5A28VDC Resistive  
 Electrical Life: 2 x 10<sup>4</sup> Operations  
 Leakage Rate: ≤5 x 10<sup>-2</sup> Pa.cm<sup>3</sup>/s  
 Dimensions: 20.5 x 10.5 x 11mm  
 Weight: 15g  
 Approved by Standards: GJB1042-90.

### SPECIFICATIONS

Part No.	Coil Voltage (Vdc)		25°C			All Temperature	
			Coil Resistance (Ω)±10%	Pick-up Voltage Max. (Vdc)	Drop-out Voltage	Pick-up Voltage Max. (Vdc)	Drop-out Voltage
	Rated	Max.					
012	12	15	180	8.8	-	10.5	-
027	27	32	900	19.8	-	24.5	-

### Outline and Dimensions:

